





アルミ支柱 強度試験比較表

| 材質(アルミ) | サイズ(断面) | 名称 | 形状 | 曲げ試験値 | 圧縮試験値 |
|----------|------------------|-------------|--|---------|---------|
| a6063-T5 | φ 60.5*1.8t*1.0t | ラジアルポールS型 |  | 2,300kg | 4,460kg |
| A6063-T5 | φ 60.5*1.5t*1.0t | ラジアルポールN型 |  | 1,600kg | 2,380kg |
| A6063-T5 | φ 60.5*2.3t*5.2t | 4か所リブ |  | 1,097kg | 1,247kg |
| A6063-T5 | φ 60.5*2.3t*5.2t | 6か所リブ |  | 1,030kg | 1,150kg |
| A6063-T5 | φ 60.5*2.3t*5.2t | 8か所リブ |  | 1,340kg | 1,600kg |
| A6063-T5 | φ 60.5*2.3t*3.9t | 2重パイプ(内φ31) |  | 1,718kg | 2,470kg |
| A6063-T5 | φ 60.5*1.2t*1.3t | 十字パイプ |  | 887kg | 755kg |
| A6063-T5 | φ 60.5*2.0t*1.5t | 十字パイプ |  | 1,430kg | 1,390kg |
| A6063-T5 | φ 60*2.0t | 丸パイプ |  | 879kg | 1,020kg |
| A6063-T5 | φ 60*3.0t | 丸パイプ |  | 1,643kg | 2,292kg |

ラジアルポールS型には、外側にリブ位置を示す目安線が2本入ってます

